





Reaming Tools



6° Taper

Reaming bit	Carbide dimension				D		Weight	Code No.
	Gauge		Front		[mm]	[in]	[kg]	
	[No.]	[mm]	[No.]	[mm]				
	8	9.5	4	8	64	2 1/2	0.90	43030
	6	11	3	11	76	3	1.25	43031
	8	12.7	4	11	89	3 1/2	1.80	43014
Pilot adapter	Thread	L		D		Weight	Code No.	
		[mm]	[in]	[mm]	[in]	[kg]		
		R25	300	11 19/64"	26	1 1/32"	3.35	53089
R28		300	11 19/64"	26	1 1/32"	3.25	53085	
R32		300	11 19/64"	26	1 1/32"	3.15	53083	

12° Taper

Reaming bit	Carbide dimension				D		Weight	Code No.
	Gauge		Front		[mm]	[in]	[kg]	
	[No.]	[mm]	[No.]	[mm]				
	8	12.7	4	9.5	89	3 1/2	2.00	43011
	8	12.7	4	12.7	102	4	2.30	43012
	8	14	4	14	115	4 1/2	2.68	43017
	8	14	4	12.7	127	5	3.50	43013
Pilot adapter	Thread	L		D		Weight	Code No.	
		[mm]	[in]	[mm]	[in]	[kg]		
		R32	255	10 3/64"	40	1 37/64"	2.4	53082
R38		265	10 25/64"	40	1 37/64"	2	53092	

12° Taper

Reaming bit(Locking thread T12)	Carbide dimension				D		Weight	Code No.				
	Gauge		Front		[mm]	[in]	[kg]					
	[No.]	[mm]	[No.]	[mm]								
	8	12.7	4	11	102	4"	3.50	43000				
	8	12.7	4	12.7	115	4 1/2"	4.30	43002				
	8	14	4	12.7	127	5"	5.10	43001				
Reaming bit	Thread	Carbide dimension				D		d		Weight	Code No.	
		Gauge		Front		[mm]	[in]	[mm]	[in]			
		[No.]	[mm]	[No.]	[mm]					[kg]		
	Hole Opener	T38	8	14	7	11	102	4"	51	2"	4.00	63043
		T38	8	14	7	12.7	127	5"	67	2 5/8"	8.80	63044
		T45	8	14	7	12.7	127	5"	73	2 7/8"	8.30	63045
		T38	8	16	7	14	152	6"	102	4"	15.4	63046
		ST58	8	16	8	14	152	6"	89	3 1/2"	13.6	63047
		T32	10	16	9	14	178	7"	76	3"	15.9	63048
		T38	10	16	10	14	203	8"	152	6"	34.5	63049